


AOL SERIES LED WALL / RECESSED



DIMENSIONS



SPECIFICATIONS

HOUSING

15" Diameter Die Cast Aluminum Housing & Open Top Frame, 1/2" Coin Plugs with O-rings for Conduit & Photocell, Textured Architectural Bronze Powdercoat Finish Over a Chromate Conversion Coating

LENS

Clear Prismatic Molded or Frost Prismatic Molded Borosilicate Glass Lens

MOUNTING

Cast-in Template for Mounting Directly Over a 4" Recessed Outlet Box, or Use 1/2" Surface Conduit.

LUMAFIT LED

Array Lumens: 3,249
Delivered Lumens: 3,005
CRI: 85
CCT: 5000K
Rated Life: 50,000 Hours
5-Year Warranty
Aluminum Boards

WATTAGE

Array: 22.7w, System: 27.2w

DRIVER

Electronic Driver, 120-277V, 50/60Hz or 347/480V, 50/60Hz; Dimmable Driver

LISTING & RATINGS

CSA: Listed for Wet Locations. IP65
Operating Temperatures: -40°C to +40°C

OPTIONS

Surge Protection
Battery Backup

Custom Colors Available Upon Request



Made in the U.S.A. of the U.S. and imported parts.
Meets Buy American requirements for ARRA.

Project Name: _____

Date: _____

Location: _____

Notes: _____


AOL SERIES LED WALL / RECESSED

ORDERING INFORMATION SELECT APPROPRIATE CHOICE FROM EACH COLUMN TO FORMULATE ORDER CODE.

Refer to example below.

SERIES	OPTICS	NUMBER OF ARRAYS	WATTAGE	BALLAST	COLOR TEMPERATURE	LENS	COLOR	OPTIONS
AOL	F Medium Beam Spread	1X One	23 23 Watts	U 120-277V H 347/480V	5K 5000K	C Clear F Frost	Z Bronze W White B Black	SF Single Fuse DF Double Fuse SP Surge Protection
ORDER:								
WLS-AOL	F	1X	23		5K			

Example: WLS-AOL-F-1X-23-H-5K-C-Z-SF



Clear Prismatic Molded Borosilicate Glass Lens



Frosted Prismatic Molded Borosilicate Glass Lens



Trim Ring, Die Cast Aluminum, 1 9/16" Outer Diameter, Allows Recessed Mounting of Fixture, Textured Bronze Finish



1919 Windsor Place
Fort Worth, TX 76110
800.622.8711

www.wslighting.com

Project Name: _____

Date: _____

Location: _____

Notes: _____

09 REV. 10/17

Specifications subject to change without notice.