


## FLL SERIES LED MEDIUM SPOT FLOODLIGHT



### DIMENSIONS



HEIGHT (A)	LENGTH (B)	WIDTH (D)
10¼"	7¼"	9"
260mm	184mm	229mm



Made in the U.S.A. of the U.S. and imported parts.  
Meets Buy American requirements for ARRA.

### SPECIFICATIONS

#### HOUSING

Die-Cast Aluminum Housing & Hinged Gasketed Lens Frame. Nickel-Plated Stainless Steel Hardware.

#### LISTING & RATINGS

CSA: Listed for Wet Locations, ANSI/UL 1598, 8750 IP55 Sealed LED Compartment.

#### FINISH

Textured Architectural Bronze Powdercoat Finish Over a Chromate Conversion Coating. Custom Colors Available Upon Request.

#### LENS

Tempered Clear Flat Glass Lens or Tempered Clear Flat Prismatic Glass Lens.

#### MOUNTING OPTIONS

Adjustable Knuckle with Angle Indicators & ½" NPS Threads or Optional Adjustable Slipfitter with Angle Indicators.

#### EASYLED LED

Aluminum Boards

#### WATTAGE

Array: 37.2w, System: 41w (175w HID Equivalent)

#### DRIVER

Electronic Driver, 120-277V, 50/60Hz or 347/480V, 50/60Hz; Dimmable Driver

#### WARRANTY

5-Year Warranty for -40°C to +50°C Environment.

Project Name: \_\_\_\_\_

Date: \_\_\_\_\_

Location: \_\_\_\_\_

Notes: \_\_\_\_\_

# FLL SERIES LED MEDIUM SPOT FLOODLIGHT

## ORDERING INFORMATION SELECT APPROPRIATE CHOICE FROM EACH COLUMN TO FORMULATE ORDER CODE.

Refer to example below.

SERIES	BEAM	WATTAGE	DRIVER	CCT	LENS	COLOR	MOUNTING	OPTIONS	ACCESSORIES
<b>FLL</b>	<b>F</b> Medium Flood, 110°H x 100°V, NEMA 7H x 7V <b>I</b> Spot Flood, 27°H x 27°V, NEMA 4H x 4V	<b>1X37</b> 37w	<b>U</b> 120-277V <b>H</b> 347/480V	<b>4K<sup>1</sup></b> 4000K <b>5K</b> 5000K	<b>C</b> Clear Flat Glass Lens, <b>P<sup>1</sup></b> Clear Flat Prismatic Glass Lens	<b>Z</b> Bronze <b>C<sup>2</sup></b> Custom	<b>KN</b> ½" NPS Knuckle Included. <b>SF</b> Slipfitter	<b>SF</b> Single Fuse <b>DF</b> Double Fuse <b>SP</b> Surge Protection	<b>FLPTFZ</b> Die-cast Post Top Fitter for 2¾" to 3½" Poles, Bronze Powdercoat Finish, Three (3) ½" Coin Plugs <b>FLSTK</b> Heavy Duty Ground Stake, Built-in Wiring Compartment with ½" NPS Threaded Fitting, Black Plastic <b>FL45GSZ</b> Glare Shield, Aluminum, Bronze Powdercoat Finish, Includes Hardware <b>FL45LG</b> Clear Polycarbonate Vandal Resistant Guard, Includes Hardware. <b>FL45WG</b> Wire Guard, Stainless Steel, Includes Hardware <b>NA</b> No Accessories

### ORDER:

<b>WLS-FLL</b>		<b>1X37</b>							
----------------	--	-------------	--	--	--	--	--	--	--

Example: WLS-FLL-F-1X37-U-4K-P-C-KN-SP-NA

### FOOTNOTES:

- 1 For F Optics only
- 2 Contact sales associate




FLPTFZ



FLSTK



FL45GSZ



FL45WG



FL73SFXZ

**WLS** LIGHTING SYSTEMS

1919 Windsor Place  
Fort Worth, TX 76110  
800.622.8711

www.wslighting.com

Project Name: \_\_\_\_\_

Date: \_\_\_\_\_

Location: \_\_\_\_\_

Notes: \_\_\_\_\_

09 REV. 10/17

Specifications subject to change without notice.